

Part Number: 6616

XTC-6000 thin client

Performance Class Thin Client

The XTC-6000 offers a combination of high performance and expandability. Powered by a 1.6GHz VIA Eden ULV processor, this unit is powerful, energy efficient and secure.

Designed for easy expansion and capable of dual monitors and rich multi-media graphics, the XTC-6000 provides a superior end user experience.



✓ XPe Operating System	✓ Centralized Management
✓ No Moving Parts	✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant
✓ Multiple Level Lock Down Feature with Protected File System	✓ Wide Screen Support
✓ IE6 (*7/8 available upon request)	✓ 1920 X 1200 Maximum Resolution
✓ Supports RDP, ICA and VDI Deployment	✓ Built-in Kensington Security Lock
✓ Energy Efficient	✓ Dual and Quad Monitor option
✓ BOSaNOVA Secure 5250 Emulation	✓ WES (XPe SP3) available upon request

**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**



System

Operating System	XPe SP2 (WES (XPe SP3) 2009 available upon request)
Form Factor	Compact case
Management	10ZiG Management Software
Processor	VIA Eden ULV 1.6 GHz
Browser	IE6 (**7 or 8 available upon request)
Video Resolution	Up to 1600 x 1200 x 32 bit color
Monitor Support	Dual and Quad Monitor optional
Wide Screen Support	Yes

Memory

RAM (Stand/MAX)	512MB/2GB
Storage (Stand/MAX)	512MB/16GB

Software Configuration

Host Access (BOSaNOVA Secure)	Supports TN5250e, SSL and SSO
ICA	Version 12.1 with HDX
RDP	6.1 (RDP 7 available on WES)
Client Software	<ul style="list-style-type: none"> Adobe Acrobat Viewer Adobe Flash Player MS Office Viewers 2003 (2007 available upon request) Microsoft Outlook Express Windows Media Player Shockwave Sun JVM & MS Java VNC Shadowing

VDI Clients	Optional Quest vWorkspace, Leostream, Citrix XenDesktop HDX, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer
--------------------	--

Dimensions

Device	2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm
Weight	3.7 lbs. (1.7kg)

Audio

Mic In/Line Out	•
Speaker	x 1 (built-in 1W internal Speaker)

Management

10ZiG Remote Manager	•
Various Client Configurations	•
Shadow Terminals	•
Status Indication	•
Power on, Log off, Reboot and Shut down	•
Task Scheduler	•
Cloning of Terminals	•
Group Operations	•
Update of Firmware	•
Recover Image	•
Configuration of Various Connection Types including 5250	•

Ports

USB Ports	Type 2	4
PS2 Port	Keyboard and mouse via 'Y' cable	
Serial Port	(D Sub, 9 Pin Male Connector)	2 ***
Parallel Port	1***	
Video Ports	1X DVI & 1 X VGA	

Environmental

Operating Temperature	0° ~ 40°C 32° ~ 104°F
Operating Humidity	20% ~ 90% non-condensing

Power

Consumption	14 watts average
AC/DC Adapter	Included

Networking

	Autosensing, 10/100/1000 Ethernet, RJ-45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option.
--	---

Compliance

	RoHS
	WEEE
	CE
	FCC

Features

Security Features	<ul style="list-style-type: none"> Kensington Security Lock Slot Auto start/auto-restart connection, Multiple level lock-down user interface Administrative and user passwords
Language Support	US, UK English, German, French, Swedish and others by request

Ordering Information

PID	Description
6616NE	XTC 6000, XPe, IE6 SP3, Sun JVM & MS Java, RCP, ICA, Shockwave, Flashplayer, Optical Mouse, Adobe Acrobat Viewer, MS Office Viewers, MS Outlook Express and Windows Media Player.
6616	Featured software from 6616NE plus BOSaNOVA Secure 5250 Emulation
9001	USB to Centronics
9011	PCI Expansion Card (Serial and Parallel Port)
9010	Internal Wireless (802.11 b/g/n + Cisco)
8122b	122-Key Driverless PC Keyboard
8104b	104-Key PC Keyboard
8008	1 GB DOM (Call for Customization and other Embedded Applications)
8010	Quad video support includes DVI & VGA Ports & 1GB Dom

*VT320, VT420, VT52, WYSE60, WYSE60/AIF, VAX/AIX, LINUX, HP70094/8, HP70092/6, HP2392A
 *** One parallel and one serial port available with optional PCI card (9011)

